



For Pleasure and More.

12.1" TFT LCD Monitor

Model	Mechanism	Bezel color	Touch Type	Touch Interface
121TAAY-WT	Desktop stand	White	-	-
121TAAY-WRC	Desktop stand	White	Resistive	RS232
121TAAY-WRU	Desktop stand	White	Resistive	USB
121TAAY-WSC	Desktop stand	White	SAW	RS232
121TAAY-WSU	Desktop stand	White	SAW	USB
121TAAY-BK	Desktop stand	Black	-	-
121TAAY-BRC	Desktop stand	Black	Resistive	RS232
121TAAY-BRU	Desktop stand	Black	Resistive	USB
121TAAY-BSC	Desktop stand	Black	SAW	RS232
121TAAY-BSU	Desktop stand	Black	SAW	USB



LCD Display		12.1" TFT active matrix panel
Display Size		275.0(W)x199.0(H) mm
Pixel Pitch		0.3075(H)x0.3075(V) mm
Max. Resolution		SVGA 800x600
Contrast Ratio		200:1 (typical)
Lamp Life		20000hr (MTBF)
Brightness		210 cd/m2
Response Time		50 ms (Tr + Tf)
Display Color		16M
Viewing Angle	L/R	+45°~-45° (typical)
	U/D	+10°~-30° (typical)
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/66/70/72/75/85 Hz)
		SVGA 800x600 (60/70/72/75/85 Hz)
Signal Connector		15 Pin Mini D-sub
Upper Control		Power Switch, Menu, Select (Up, Down)
OSD		Brightness, Contrast, R.G.B. Contrast, Frequency, Phase, H-position, V-position, Load Mode, Load Default
Plug & Play		DDC1/2B compatible
Power	Form	AC/DC Adapter
	Input	AC 90-264V, 50-60Hz
	Output	DC 12V/3A
	Consumption	22W
Operating Temperature		0°C-40°C (32°F-104°F)
Conditions	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Temperature		-20°C-60°C (-4°F-140°F)
Conditions	Humidity	10%-80% (no condensation)
Certification		C-UL, FCC, TUV/GS, CE

www.hi-mind.com

France Hi-Mind Technologies, SAS. sales-france@hi-mind.com
 Taiwan Hi-Mind International, Inc. sales-global@hi-mind.com
 UK Hi-Mind Ltd. sales-europe@hi-mind.com