

HMP-High-Definition Robust Digital Signage System

High-definition MPEG-1/2/4 decoder supporting Flash, PowerPoint, and Windows Media imports

Connected across wide area networks and local area networks

Reliable 24x7x365 operations

Technical Specification

Processor	IAN510 Multimedia Networking Sigma Designs Media Processor Dual Processor Architecture
Networking	IEEE 802.3 Ethernet 10/100 Base-T
Video Performance	1024x768 (XGA) 1280x720 (720p)
Video Output	DVI, VGA, S-video (monitor not included)
Playback Control	Trimode (WAN/LAN/SI) interface
Supported Media	Formats MPEG-1 MPEG-2 MP@HL MPEG-4 Part 2 WMV9/VC-1 MP@ MPEG-4 AAC-LC WMA9 audio
Screen/Power Saver	DPMI screen on/off control
Security	HTTP Authentication
Storage Medium	Compact Flash Type I/II memory card option (not included) 2.5" IDE HDD option (not included)
Dimensions	8 1/2" x 5" x 1"
Dimensions (L x W x H)	133.5 mm x 113.5 mm x 25 mm 5 1/4 x 4 1/2 x 1
Weight	3 lbs
Power Requirement	100 to 240 VAC, 50/60 Hz
Power Consumption	24W max
Operating Environment	Recommended: 15 to 35°C, 20 to 80% RH Maximum: 15 to 35°C, 5 to 95% RH Storage: -30 to 65°C

